



## FACTORY GUITAR SETUP MEASUREMENTS

NECK RELIEF • ELECTRIC GUITARS			
FINGERBOARD RADIUS		STRING HEIGHT AT 17 <sup>TH</sup> FRET	
FINGERBOARD RADIUS	RELIEF AT 8 <sup>TH</sup> FRET	BASS SIDE	TREBLE SIDE
9.5" to 14"	.010"	4/64"	4/64"
16"	.008"	4/64"	4/64"

PICKUP HEIGHTS • ELECTRIC GUITARS			
PICKUP TYPE	POSITION	BASS SIDE	TREBLE SIDE
Humbucker	Neck	3/32"	4/64"
	Bridge	3/32"	4/64"
Tele Single Coil	Neck	5/64"	4/64"
	Bridge	5/64"	4/64"
P90	Neck	3/32"	4/64"
	Bridge	3/32"	4/64"

NECK RELIEF • ACOUSTIC GUITARS			
FINGERBOARD RADIUS		STRING HEIGHT AT 14 <sup>TH</sup> FRET	
FINGERBOARD RADIUS	RELIEF AT 8 <sup>TH</sup> FRET	BASS SIDE	TREBLE SIDE
9.5" to 14"	.010"	6/64"	5/64"
14" to 16"	.008"	6/64"	5/64"

NECK RELIEF • ELECTRIC BASS			
FINGERBOARD RADIUS		STRING HEIGHT AT 17 <sup>TH</sup> FRET	
FINGERBOARD RADIUS	RELIEF AT 8 <sup>TH</sup> FRET	BASS SIDE	TREBLE SIDE
9.5" to 14"	.012"	6/64"	5/64"
16"	.010"	6/64"	5/64"